

NEXT GENERATION VIDEO RECORDING

ION is a multipurpose geospatial video recorder that can be utilized for a wide range of land, sea and air missions. It offers simultaneous recording of multiple HD-SDI video channels, one channel of analog video, audio and metadata. With H.264 recording and playback in real-time, you get complete confidence in the content being recorded.



ION FEATURES

- Record two channels of HD-SDI and one channel of analog video simultaneously.
- Monitor recordings and review video on the device in real-time, even while recording.
- Never miss the action – ION's configurable record buffer captures video prior to the record button being pressed.
- Know where your video was recorded: Capture KLV MISB/STANAG 4609 compliant metadata.
- Use inexpensive SD or USB memory to capture hours of HD quality video with metadata.
- Automatically trigger recordings based on events such as skids-off or hoist cam activation.
- With built-in video scalers, framerate conversion, plus flexible encoding parameters, ION is a great solution for any video problem.
- Embed GMTI RADAR data, AIS, ADS-B, etc. into transport streams.
- DO-160 qualified and NVG certified.

BUILT-IN DISPLAY LETS YOU RECORD WITH CONFIDENCE



Featuring a full-color, night vision compliant display, ION provides more screen real estate than any other geospatial video recorder in its class. Its compact and rugged design means it can be used in a variety of locations, and its simple user interface allows for a wide range of applications.



UNRIVALED SUPPORT AND WARRANTY

- 3-Year Hardware Warranty
- No Annual Fee for Support or Software Updates
- 24 Hour Warranty Replacement (USA)
- 1-Year Money-Back Guarantee

ION SPECIFICATIONS

FRONT CONNECTIONS

USB 3.0 (x2)
SD Card (x2)

REAR CONNECTIONS

HD-SDI Input (x2)
Single channel, 3G-SDI (1080p60) input supported
Analog Video Input
HD-SDI Output
3G-SDI (1080p60) output supported
Gigabit Ethernet
RS-232 (x5)
RS-422 (x2)
Audio In (x2)
Audio Out (x2)
GPIO (x2)
USB 2.0
ARINC 429 (x2) IN, 1 Out (optional)
28 VDC Input, Panel Dimming

STORAGE

External - Continuous uninterrupted recording with Hot-Swap

WEIGHT

2.6 Lbs (1.22 Kg)

SIZE

7" L x 5" W x 1.875" H
177.8 mm x 127 mm x 47.6 mm

2.7.22

**SHOT
OVER**
SHOTOVER.COM

SHOTOVER HQ
5660 Airport Blvd., Suite 101
Boulder CO, 80301

NEW ZEALAND
133 Glenda Drive
Queenstown, 9300

LOS ANGELES
16303 Waterman Drive
Van Nuys CA, 91406

GERMANY SERVICE CENTER
Am Technologiepark 1-5, Gebäude 4,
Maintal Germany, 63477

SALES
+1 720 680-2457
info@shotover.com

CUSTOMER SUPPORT
+1 720 440-3300 | Dial 1 when prompted
support@shotover.com