SHOT M1 CREATIVE



UNMATCHED 6-AXIS CAPABILITIES

From fast-paced production shoots to wildlife documentaries, the M1's unrivaled look-down capability, superior range of movement, and next-generation SHOTOVER technology provide filmmakers with unparalleled flexibility to bring their visions to life.



M1 CREATIVE FEATURES

- 6-axis gyro stabilization provides unmatched look-down capability and versatility
- No ITAR restrictions or EAR licensing requirements
- Auto or Steerable horizon with the most advanced steering capabilities on the market
- Open platform design allows for the integration of new payloads and other cutting-edge technology as it comes to market
- Windowless operation option for brilliant imagery without reflections
- Custom color scheme and logo imprint options
- Shoot in adverse weather conditions with SHOTOVER accessories including rain spinner, desiccant value, and demist fan



SHOTOVER HQ 5660 Airport Blvd., Suite 101 Boulder CO, 80301

NEW ZEALAND 133 Glenda Drive Queenstown, 9300 LOS ANGELES 16303 Waterman Drive Van Nuys CA, 91406

GERMANY SERVICE CENTER Am Technologiepark 1-5, Gebäude 4, Maintal Germany, 63477 SALES +1 720 680-2457 info@shotover.com

CUSTOMER SUPPORT +1 720 744-3300 | Dial 1 when prompted support@shotover.com

GIMBAL SPECIFICATIONS

STABILIZATION

6-axis with no gimbal lock

High performance non-ITAR sensors

Distributed Multi-processor closed loop servo control system

Proprietary gimbal control algorithms

GIMBAL FIELD OF VIEW

Pan: 360 degrees continuous (via electrical and optical rotary joints)

Tilt: +50 to -110 degrees

Roll: +/-75 degrees (steerable or auto horizon)

Max slew rate: 100 deg/sec

WEIGHT

Turret without payload 18.9kg (41.6lbs) + payload Operator control unit 2.5kg (5.5lbs)

External cable set: 1.0kg (2.2lbs)

POWER

24-60 VDC

10 Amps Max Draw (at 28V)

ENVIRONMENTAL

Operating Temperature: -20 to +40 C / -4 to 104 F

GIMBAL CONTROLLER

Customizable video overlay (Monitor Output)
Fully integrated camera control units; Ikegami RM-70F,
Sony RM-B750, & NEC
Integrated 15VDC 120W Monitor Power Supply
LED display with customizable switches
Custom control layouts available upon request



CAMERA & LENS OPTIONS

	Fujinon Cabrio ZK 14-35	Fujinon Cabrio ZK 19-90	Fujinon Cabrio XK 20-120	Fujinon Cabrio ZK 85-300	Fujinon Premier 18-85	Fujinon Premista 28-100	Fujinon Premista 80-250	Canon CN7x17 (17-120)	Canon CN10x25 (25-250)	Canon CN-E 30-300	Canon CN20x50 (50-1000)	Angenieux 45-120 #	Angenieux 15-40 / 28-76 #	Angenieux 25-250 HR
RED DSMC2 **	•	•	•	•	•	•	•	•	•	•	•	•	•	
RED Komodo ~	•	•	•	•	•	•	•	•	•	•	•	•	•	
RED V-Raptor	•	•	•	•	•	•	•	•	•	•		•	•	
ARRI Mini														
ARRI Mini LF	•	•	•			•	•	•	•	•			•	
Sony F55														
oonly 1 oo														
Sony Venice #														

Key:

Scheduled for Development

** Jetpack SDI Expander required

~ RF len mount adaptor required

Not Tested

Please note cameras and lenses are not included and this is not an all inclusive list of all compatible cameras and lenses.

UNRIVALED SUPPORT AND WARRANTY

- Includes 2-Year Hardware Warranty
- No Annual Fee for Support or Software Updates
- 24/7 Service and Support Line





5660 Airport Blvd., Suite 101 Boulder CO, 80301

NEW ZEALAND 133 Glenda Drive Oueenstown, 9300 LOS ANGELES 16303 Waterman Drive Van Nuys CA, 91406

GERMANY SERVICE CENTER Am Technologiepark 1-5, Gebäude 4, Maintal Germany, 63477 SALES +1 720 680-2457 info@shotover.com

CUSTOMER SUPPORT +1 720 744-3300 | Dial 1 when prompted support@shotover.com